

Multifunctional scale S601 - 150kg



STRUCTURE

- Epoxy steel
- Stainless steel AISI 304

PROTECTION

- Watertightness IP56
- Load cell overload (4)

USE

- From +5° to +40°C
- Humidity < 60%

INPUT VOLTAGE



- Releasable
- 100-240V, 50/60Hz
12V 800mA

BATTERY

- Rechargeable
6V5.0Ah
- Autonomy 40-70h

TRAY

- (W) 400 x (D) 500 x (H) 127mm
- (W) 500 x (D) 600 x (H) 140mm
- (W) 600 x (D) 800 x (H) 170mm



DISPLAY

- Height : 25 mm
- LCD backlit



FUNCTIONS

- Weighing, taring, precise counting
- Totalization
- 20 tare memories
- Counting with reference quantity 1,2,5,10...pcs
- 99 reference weight memories
- RS232

Thermal printer



Tél : 01 34 53 35 35
Fax : 01 39 85 31 32
Mail : info@manutan.fr
www.manutan.fr

	Weighting Capacity (kg)	Readability (g)	Tray (mm)	Certification
A016147	150kg	20g	500 x 400	Local adjustment
A169679				UKAS (Cofrac)
A016148	150kg	20g	600 x 500	Local adjustment
A169780				UKAS (Cofrac)
A016149	150kg	50g	800 x 600	Local adjustment
A169788				UKAS (Cofrac)